

Client:			
Manufacturer:		Model:	
Description:			
Test Standard:			
<input type="checkbox"/> ANIS/ISEA Z89.1	<input type="checkbox"/> AS/NZS 1801	<input type="checkbox"/> CAN/CSA Z94.1	<input type="checkbox"/> EN 397
Type of Head Protector:			
<input type="checkbox"/> Type I / Type 1	<input type="checkbox"/> Type II / Type 2	<input type="checkbox"/> Type 3	
<input type="checkbox"/> Class C	<input type="checkbox"/> Class G (2200 volts)	<input type="checkbox"/> Class E (20,000 volts)	
Material:			
<input type="checkbox"/> PE	<input type="checkbox"/> PC	<input type="checkbox"/> HDPE	<input type="checkbox"/> Other: _____
Suspension Type:			
<input type="checkbox"/> Ratchet	<input type="checkbox"/> Pin-lock	<input type="checkbox"/> Other: _____	
<input type="checkbox"/> 6 pt.	<input type="checkbox"/> 4 pt.	<input type="checkbox"/> Other: _____	
Shell Type:			
<input type="checkbox"/> Non-vented	<input type="checkbox"/> Vented		
Type of Test:			
<input type="checkbox"/> Compliance Testing	<input type="checkbox"/> R&D Testing		
Markings and User Instructions Requirements:			
<input type="checkbox"/> Assess Markings and User Instructions	<input type="checkbox"/> Do Not Assess Markings and User Instructions		

Optional Requirements:	
ANSI/ISEA Z89.1	
<input type="checkbox"/> 7.3.1	Reverse Wearing
<input type="checkbox"/> 7.3.2	High Visibility
<input type="checkbox"/> 7.3.3	Higher Temperature (60°C ± 2°C)
<input type="checkbox"/> 7.3.4	Lower Temperature (-30°C ± 2°C)
AS/NZS 1801	
<input type="checkbox"/> 4.7	Resistance to Penetration (mfg. option)
<input type="checkbox"/> 2.2.2	Sweatbands for Dusty Work
<input type="checkbox"/> 3.3.5	Retaining Strap for Special Purposes (Type 3)
<input type="checkbox"/> 4.10	Retaining Strap Strength - or -
<input type="checkbox"/> 4.11	Retaining Strap Strength w/ Specified Breakpoint
<input type="checkbox"/> 3.4.2	Lamp Bracket and Cable Clip
<input type="checkbox"/> 3.4.3	Retaining Strap (chinstrap)
<input type="checkbox"/> 3.4.4	Earmuffs and Means of Attachment
<input type="checkbox"/> 3.4.5	Eye and Face Protection
<input type="checkbox"/> 3.4.6	Ear and Neck Protection (Type 2 & 3)
<input type="checkbox"/> 3.5.3	External Vertical Distance
CAN/CSA Z94.1	
<input type="checkbox"/>	Reverse Wearing
EN 397	
<input type="checkbox"/> 5.2.1	Very Low Temperature (-20°C ± 2°C or -30°C ± 2°C)
<input type="checkbox"/> 5.2.2	Very High Temperature (150°C ± 5°C)
<input type="checkbox"/> 5.2.3	Electrical Properties
<input type="checkbox"/> 5.2.4	Lateral Deformation
<input type="checkbox"/> 5.2.5	Molten Metal Splash